



The NIVOflex –mot series
As standardized single modules,
Motorized platforms serve for the
Construction of total areas, which
can be infinitely adjusted to various
height-configurations.
NIVOflex-mot is available in two
designs with 130 mm and 500 mm
net construction heights. Each modu-
le has its own electric motorized dri-
ve.

Along with many standard sizes, the
Adaptable variation system also
offers special solutions, options and
an extensive accessory program.

Areas of use

- With new constructions
- as subsequent installation with struc-
tural alterations and reconstructions
- in theatres
- in multipurpose halls
- in concert halls
- in conference rooms or banks, insu-
rance companies and the industry
- in exhibition and presentation halls
- in the hall sector
- for spectator benches
- in the stage sector
- as scene areas
- as a concert podium
- as transport or equalization podiums
- and in many other branches

- ❑ **optimal hall usage**
- ❑ **maximum efficiency**
- ❑ **minimum installation**

NIVOflex-mot[®] 130

With an installation depth starting
with 180 mm, NIVOflex-mot 130
can also be used where the building
or the budget does not allow for-
deep installation pits or fountain bore
holes. With this, the motorized plat-
form can also be subsequently instal-
led without any problems.



NIVOflex-mot[®] 500

The method of construction offers lar-
ger (wider) single module surfaces
with an installation depth of 580
mm.

Where these installation dimensions
can be realized, e.g. in single-story
or ground level halls, NIVOflex-mot
500 offers an economic alternative.

