



NIVOflex®-Stabilo

The largest selling scissor-type platform



NIVOflex®-Stabilo. More than 150,000 platforms are in daily use.

Product description

A lighter scissor-type platform with aluminium upper frame and a scissor-type system in steel – light construction for the general events area and the presentation of products. Optimal security of stand. The large-volume load-sharing feet provide a low pressure-to-area contact and make the NIVOflex®Stabilo platform system suitable for sensitive floors. The upper frame contains an integrated multifunction track for the binding of the platform elements together and for the fastening of accessories like curtains, banisters, product descriptions, containers for prospectuses and catalogues, price tags and much more. The 22 mm strong load-bearing surface is available in various surfaces.

- ☐ **variable height scissor-type construction**
- ☐ **fast assembly/dismantling - angular setting possible**
- ☐ **available with various surfaces**
- ☐ **floor-protecting load-distributor - secure stand**
- ☐ **tested static equilibrium in accordance with DIN 4112, 1055, 15920**

Assembly and dismantling

The scissor-type construction is conveniently unbolted by the Bowden cable system. Thus the desired height can be quickly set up to 1 m ranging in stages up to 20 cm (on request also in theatre stages of 16²/₃ cm). The catch of the arresting device thereby clicks into it audibly and visibly. The platform allows the setting of a slanting stage.



Guide carriages with locking device.



Height adjustment through Bowden cable system.

Areas of operation

Presentation of events

Presentation of products



All construction parts are screw fastened.

Technical data NIVOflex®-Stabilo

- Dimensions 2 m x 1 m
- Load 750 daN / m²
- Maximum construction height 100 cm
- Weight 56 kg
- Storage height 20 cm
- Load-bearing surface 22 mm